

Distributor for Crystal Fountains

Custom Fountains, Inc.

1-800-563-5628 - 513-398-1447 - Fax 513-398-5141



NGA series

Fan Jet



Specification:


Construction shall be cast bronze, machined brass and copper with DEFO integral swivel base.

Note:

- (for optimum effect)
 1. Requires non-turbulent water supply.
 2. Use shaded chart section.

Function

A clear fan-shaped display. Ideal when angled to 45° and used as a peripheral effect in a location free of wind. **Not water level dependent.**



Dimensions

Performance

DEFO no.	suction strainer openings required	a dim.	b dim.	inlet (npt) (bsp)	throw	2'	3'	5'	6'	8'	10'
NGA-100	.125"	4"	2½"	1"	gpm head spread height	3 3' 20" 28"	5 5' 56" 45"	5 7' 101" 64"			
NGA-150	.250"	5½"	3¾"	1½"	gpm head spread height	11 3' 6" 28"	14 4' 24" 42"	18 6' 35" 64"	20 8' 79" 75"	23 10' 142" 108"	
NGA-200	.325"	8¾"	4½"	2"	gpm head spread height	9 2' 5" 18"	11 3' 11" 24"	14 4' 24" 36"	17 6' 48" 56"	19 7' 48" 56"	21 8' 70" 70"

4300 State Route 42 - Mason - Ohio - 45040